



## Technical specifications

- Two switches as standard
- Nominal pressure: 16 bars (20 bars cold water only)
- Hydraulic shell test pressure: 24 bars
- Hydraulic seat test pressure: 17.6 bars
- Temperature range: - 10°C to +100°C
- Suitable media: Water, Oil, gas

DN (mm)	Reference	A mm	B mm	C mm	D mm	Do mm	E mm	F mm	K mm	J mm	H mm	L mm	Weight Kg
50	VANNPAPW2E	191	80	42	53	58	115	115	145	110	8	90	8.3
65	VANNPAPW21/2E	203	91	45	53	73	115	115	145	110	14	110	8.3
80	VANNPAPW3E	211	95	45	53	83	115	115	145	110	19	126	9.1
100	VANNPAPW4E	230	115	50	53	102	115	115	145	110	26	154	10.2
150	VANNPAPW6E	255	138	56	53	102	115	115	145	110	48	210	13.9
200	VANNPAPW8E	271	170	60	80	202	175	165	200	160	71	265	24.7
250	VANNPAPW10E	326	198	68	80	252	175	165	200	160	92	320	33.4
300	VANNPAPW12E	326	198	68	80	302	175	165	200	160	111	370	42.3

## Notes

1. Conforms to BS EN 593, MSS SP-67
2. Bolt circles are carefully designed to fit the following flange types BS EN 1092, PN16, BS 10 D/E, ANSI 125
3. Top flange conforms to ISO 5211/1 pour bride.