

## 10-26

### New generation of impact sprinkler.

#### FEATURES

- 1/2" male threaded inlet
- Trajectory angle: 26°
- Front nozzle from Ø2.5 to 3.5 mm
- Plug or rear nozzle of Ø2.0 mm
- Discharge from 0.39 to 1.09 m³/h
- Radius from 8.90 to 11.10 meters
- Working pressure: 2 to 3.5 bars
- Packaging: box of 100 units.

#### USE

- Overhead irrigation for solid set systems of any kind.
- Specially designed for vegetables, horticulture, nurseries.
- Private and public landscape irrigation.

#### SPECIALITIES

- Water turbulence reducing system designed for longer radius and better water distribution.
- Quick fit nozzles (1/4 turn).
- Colour coded nozzles with built in vane for better radius throw
- Stainless steel axle for greater resistance to wear on sandy soils and long use.
- Security cap of the arm spring for a regular and efficient irrigation.
- Security ring of the rotation mechanism to avoid sand problems and wear.
- Large choice of nozzles to allow very precise water precipitation.

#### HOW TO FIT\*

- Put Teflon on the sprinkler base (do not put it on washers)
- Check that the sprinkler base does not touch the inner part of the connector that will block rotation.
- Triangular spacing usually given from 6 to 12 meters.
- Front nozzle with key below centre hole.
- Do not forget to install special ring on rear nozzle or plug
- Rear nozzle or plug to be fitted on sprinkler in respect of internal elbow to allow water flow.
- Recommended to be fitted on Rolland stake S10 or P10 risers.

\* Installations and specifications done in the area are made under the responsibility of the installer according to the area Rules and Authorities.



#### 10-26 with one nozzle

Nozzle size (mm)	Pressure (bar)	Discharge* (l/h)	Radius* (m)
2.5 E (Grey x Black)	2.5	396	8.90
	3.0	408	9.20
	3.5	452	9.50
3.0 E (Orange x Black)	2.5	560	9.20
	3.0	600	9.70
	3.5	640	10.00
3.5 E (White x Black)	2.5	816	10.20
	3.0	876	10.80
	3.5	928	11.30

#### 10-26 with twin nozzles

Nozzles size (mm)	Pressure (bar)	Discharge* (l/h)	Radius* (m)
2.5 E X 2,0 (Grey x Blue)	2.5	528	8.80
	3.0	564	9.20
	3.5	612	9.40
3.0 E X 2,0 (Orange x Blue)	2.5	620	9.10
	3.0	736	9.50
	3.5	784	9.80
3.5 E X 2,0 (White x Blue)	2.5	936	10.00
	3.0	1040	10.60
	3.5	1084	11.10

\* To be used for informational purpose only.