

6CTB

Easy irrigation
for greenhouses



FEATURES

- 1/2" male threaded inlet
- Trajectory angle: 7°
- Front nozzle from Ø1.8 to 2.5 mm
- Discharge from 0.75 to 3.53 m³/h
- Radius from 12.80 to 18.0 meters
- Working pressure: 1.5 to 3.5 bars
- Packaging: box of 200 units.

USE

- Pendent impact sprinkler for greenhouses.
- For nurseries, vegetables mainly.

SPECIALITIES

- Impact sprinkler.
- Large choice of nozzles.
- Screw nozzle to adjust droplets size and radius..
- Can be used with simplified filtration system.
- One line of sprinklers required for 8 meters large greenhouses.
- Easy to use.
- Better durability than rotor system on hard water.

HOW TO FIT**

- Put Teflon on the sprinkler base (do not put it on springs)
- Check that the sprinkler base does not touch the inner part of the connector that will block rotation.
- Spacing between sprinkler from 3.5 to 5 meters.
- One line up to 9 m large greenhouses.
- To install on Saddle tee.
- Use rigid pipe only (PVC for greenhouses or other rigid pipes). Do not install on flexible pipe (PE, ...).
- To install only in pendent position.

** Installations and specifications done in the area are made under the responsibility of the installer according to the area Rules and Authorities.

Screw nozzle size (mm)	Pressure (bar)	Discharge* (l/h)
1.8 BJ	-	-
	2.5	175
2.0 BJ	3.5	200
	1.5	180
2.5 BJ	2.5	220
	3.5	248
	1.5	240
	2.5	326
	3.5	386

* To be used for informational purpose only.