

E11



FEATURES

- Impact sprinkler.
- 1" female threaded inlet
- Trajectory angle: 30°
- Nozzle from Ø3.5 to 4.5 mm
- Discharge from 0.73 to 1.48 m³/h
- Radius from 12.80 to 18.0 meters
- Working pressure: 3.0 to 4.5 bars
- Packaging: box of 10 units.

USE

- Pop up impact sprinkler for landscape applications.
- Landscape, private gardens, horse racing, sports-fields, golf courses.

SPECIALITIES

- Brass sprinkler inside.
- Screw nozzle to adjust droplets size and radius.
- ABS casing.
- No maintenance required.
- Can be easily repaired. All spare parts can be ordered.

HOW TO FIT**

- Put Teflon on the sprinkler base.
- Spacing between sprinkler from 6.0 to 16.0 meters.
- Triangular spacing recommended when possible.
- Ask your installer for fitting.
- Make drainage below the casing with adequate gravel.

** Installations and specifications done in the area are made under the responsibility of the installer according to the area Rules and Authorities.

E11 (full circle)

Nozzle size (mm)	Pressure (bar)	Discharge* (l/h)	Radius* (m)
3.5	2.0	660	11.50
	3.0	790	11.90
	4.0	950	12.60
4.0	2.5	870	11.00
	3.0	1040	11.50
	3.5	1210	12.30
4.5	2.5	1190	11.50
	3.0	1310	12.20
	3.5	1480	13.00

Also exist:
Front nozzle : Ø3.7 - 3.8 - 4.2 - 5.0
Rear nozzle : Ø2.0 - 2.5

E11S (part circle)

Nozzle size (mm)	Pressure (bar)	Discharge* (l/h)	Radius* (m)
4.0	2.0	870	11.00
	3.0	1040	11.50
	4.0	1210	12.30
4.5	2.0	1190	11.50
	3.0	1310	12.20
	4.0	1480	13.00

* To be used for informational purpose only.